

Biologically-Inspired Adaptive Dynamic Walking of the Quadruped on Irregular Terrain *

Yasuhiro Fukuoka, Hiroyuki Nakamura and Hiroshi Kimura

Graduate School of Information Systems, Univ. of Electro-Communications
5-1 Chofu-ga-oka 1-chome, Chofu City, Tokyo 182-8585, JAPAN

Abstract

In the present study we attempt to induce a quadruped robot to walk dynamically on irregular terrain by using a neural system model. In this paper, in order to realize walking on irregular terrain, we propose the biologically-inspired control method consisting of four levels, those are, "adaptive control using a muscle stiffness model", "adaptive control based on vestibular sensation", "parameters adjustment based on somatic sensation and reflexes coordination based on vestibular sensation", and "motion switching based on visual information". As results of basic experiments of each level, we show that a robot can walk on a single bump, and walk up and down a slope by using such adaptive control method. We also show that the functions as a lower controller in the Drew's physiological model for leg control mechanism based on visual information are satisfied by a CPG characterized by mutual entrainment with a musculo-skeletal system, automatic interpolation, and self stabilization. These findings suggest a simple method for producing autonomous adaptive dynamic walking on terrain of high degree irregularity.

1 Introduction

Many previous studies of legged robots have been performed. About dynamic walking on irregular terrain, biped [1, 2] and quadruped[3] robots have both been studied. Most of these earlier studies employed precise models of a robot and an environment and involved planning joint trajectories as well as controlling joint motions on the basis of an analysis of the models. However, when a legged robot moves quickly in a variety of places, a method consisting of modeling, planning and control such as these is not effective and not

adaptable for the reason identified by Brooks(1991) in his proposal of the behavior-based approach.

On the other hand, it is well known that the motions of animals are controlled by internal nervous systems. Many biological studies of motion control have therefore been done. It is generally accepted that walking of animals is generated by combination of a rhythm pattern generator (Central Pattern Generator:CPG) and reflexes in response to the peripheral stimulus. Much previous research attempted to generate autonomously and emergently adaptable walking using such biologically-inspired control mechanism. Beer[4] was able to achieve static walking in a hexapod robot by incorporating reflexes to several sensor inputs and a few directive signals from the upper level modeled after those of an American cockroach. About two-legged mammal-type dynamic walking, it was shown by simulation that stable and flexible biped walking[5] and three dimensional bipedal stepping[6] could be realized by a global entrainment between a CPG and a musculo-skeletal system. About four-legged mammal-type dynamic walking, it was shown that neural controllers optimized by using a evolutionary method like GA[7, 8] or a reinforcement learning method[9] could generate walking of the quadruped. But dynamic walking of a real robot using CPG or neural controllers was rarely realized in these earlier studies.

In our previous studies using a quadruped robot, we realized dynamic walking on flat terrain in trot and pace gaits using a CPG alone, dynamic walking on irregular terrain using a CPG and a reflex mechanism, and running on flat terrain using a CPG and spring mechanism[10]. However, the irregularity of terrain in that study was very low and walking over terrain undulations and up steps where adaptive control based on vestibular and somatic sensation and vision is needed has not yet been realized.

In this paper, in order to realize adaptive dynamic

*Proc. of IEEE/RSJ Int. Conf. on Intelligent Robots and Systems Kyongju, pp.1657-1662, 1999.10.

walking on terrain with a high degree of irregularity, we employ four biologically-inspired control mechanisms. It is shown that such control mechanisms are effective in producing dynamic walking on irregular terrain through experiments using a quadruped robot. In comparing results of the experiments in this study to previous experiments using the conventional control method based on dynamics, we discuss our reasons for selecting such a biologically-inspired control mechanism.

Video footage of these experiments can be seen on WWW (<http://www.kimura.is.uec.ac.jp>).

2 The Quadruped Robot

The quadruped robot “Patrush” has three joints, namely the hip, knee and ankle joints, that rotate around the pitch axis. A DC motor and a photo encoder are attached to hip and knee joints and ankle joints are passive. When this quadruped robot walks dynamically in trot gait, the body motion of it is constrained on the pitch plane by two poles. For reflex mechanism, micro-switches are attached to the underside of the foot and the toe to detect contact with the floor and with fore obstacles, respectively. In addition, a rate-gyro, as an angular velocity sensor is mounted on a body as vestibule in section 4.3..

3 Walking using CPG and reflexes

As a model of CPG, we use a neural oscillator (Fig.1) proposed by Matsuoka[11] and applied to the biped by Taga[5]. A neural oscillator(N.O.) consists of two mutually inhibiting neurons, which alternately induce torque in opposite directions of contraction of the flexor and extensor muscles. Each neuron is represented by the non-linear differential equations. By connecting N.O. of each leg, the N.O.’s are mutually entrained and oscillate in a same period and with a fixed phase difference. This mutual entrainment between the N.O.’s of legs results in a gait.

Although we realized dynamic walking on flat terrain in trot and pace gait using a CPG alone, sometimes walking became unstable even on flat terrain because the supporting legs slipped. This meant that it was difficult to realize a stable walking using a CPG alone. Therefore, for dynamic walking on irregular terrain with a low degree of irregularity, we employed a control system involving a CPG and stretch and flexor reflexes[10] (Fig.2). Dynamic walking on flat terrain accomplished via use of a stretch reflex in addition to a CPG became much more stable, compared with use of a CPG alone, because stretch reflex torque assisted

in the phase transition from swinging to supporting and in preventing the supporting leg from slipping. In addition, transmission of stretch reflex torque to another supporting leg facilitated synchronization between supporting legs. Stable dynamic walking on terrain furnished with obstructions to swinging legs was made possible by the flexor reflex and the crossed extension reflex.




Fig.1 Neural oscillator. Fig.2 Reflex mechanism.

4 Adaptive Dynamic Walking on Irregular Terrain

4.1 Adaptive Control Mechanism

When we consider walking as an exchange of supporting legs, the stability of walking is nothing but the reliability of the exchange of supporting legs. Therefore, in the case of walking on irregular terrain, it is essential that:

- a swinging leg not be prevented from moving forward in the former period of the swinging leg phase and landing reliably on the ground in the latter period of this phase, and
- the angular velocity of the supporting legs around the contact points at landing moment be kept constant in spite of changes of height of the ground surface.

For (a) to be satisfied, we have already employed the reflex mechanisms, those are, the flexor reflex for the swinging motion and the stretch reflex for the landing motion[10].

In order to satisfy condition (b) above when a robot goes up and down a step or stairs, a larger torque at the hip joints of the supporting legs is required when going up and a smaller torque is required when going down. In the case that discontinuous change of

ground height is recognized by vision, the upper controller can give the directive signal to the lower controller and it is desirable that the external input to a CPG is modified in order to realize such control of angular velocity of the supporting legs as described in section 4.4.. But, in the case that continuous change of ground height like terrain undulations, bumps on terrain, and a slope exist, it is desirable that walking is adaptively controlled by lower controller without vision in order to satisfy condition (b). Therefore, we employ the following four biologically-inspired adaptive control mechanisms in order to realize dynamic walking on irregular terrain.

- (1) Adaptive control using a muscle stiffness model (Fig.3-A) for walking on terrain with a low degree of irregularity.
- (2) Adaptive control based on vestibular sensation (Fig.3-B) for walking on terrain with a middle degree of irregularity.
- (3) Adjustment of CPG's parameters based on somatic sensation and coordination of reflexes based on vestibular sensation by cerebellum (Fig.3-B).
- (4) Adaptive control based on visual information (Fig.3-C) for walking on terrain of discontinuous irregularity.

These four control mechanisms in animals are made physiologically clear to some extent and control the musculo-skeleton via a CPG and reflex mechanism at the spinal cord (Fig.3).




Fig.3 Neural system for adaptive walking

We added the adaptive controls (1), (2), and (3) into the control system consisting of a CPG and reflex

mechanism used in our previous study[10] and tried to make a quadruped robot walk on irregular terrain shown in Fig.4.




Fig.4 Irregular terrain used in experiments.

4.2 Adaptive Control Using Muscle Stiffness Model

When a muscle is stretched, a stretch reflex outputs force contracting the muscle. The stretch reflexes of extensor muscles of a supporting leg are especially important because they generate torques to support a body. It is pointed out by physiological experiments that when the length of a extensor muscle becomes large, stiffness of a stretch reflex of the muscle becomes small[12]. We call such property of a stretch reflex a “muscle stiffness model”. In this study, we assume that stiffness of a stretch reflex has a relation to the length of a muscle shown in Fig.5.

In order to improve adaptability of control performed below a spinal cord, we introduce this muscle stiffness model and try to make a quadruped robot walk on a small bump or up a slope by adjusting stretch reflexes of extensor muscles of a supporting leg. When a leg lands on a bump (Fig.6), the knee joint is bent and extensor muscles are more stretched (x_1 in Fig.5) than they are in landing on a flat floor (x^* in Fig.5). Since stiffness of a stretch reflex (S_1 in Fig.5) becomes small according to the muscle stiffness model, the bending of the knee joint is kept and a body is prevented from rising by excess reaction force from the ground.




Fig.5 Muscle stiffness model Fig.6 Walking on bumps

As results of experiments, a robot succeeded in walking on a bump 2cm in height and walking up a slope of 7 degrees (Fig.7) smoothly with a low degree

of up-and-down motion of a body by using the muscle stiffness model. In Fig.7, we can clearly see that the stiffness of the knee joint in supporting phase becomes small in walking up a slope similar to the case of walking on a bump (Fig.6) because the knee joint was more bent than it was in walking on a flat floor.




Fig.7 Results of the experiment involving walking up a slope of 7 degrees by using the muscle stiffness model. CPG output torque of the hip joint, the knee joint angle, and the knee joint stiffness of the left fore leg are shown. Positive value and negative value of CPG output torque mean swinging phase and supporting phase of the leg in CPG level, respectively. The knee joint in supporting phase in walking up a slope, for example, from 3.8 to 4.5(sec) was more bent than it was in walking on a flat floor.

4.3 Adaptive Control Based on Vestibular and Somatic Sensation

4.3.1 Walking Up a Slope Using Vestibulospinal Reflex

When a vestibule of a quadruped animal detects a inclination of the head in walking up a slope, it bends knee joints and tries to keep posture of the body flat and prevent the center of gravity from being pulled backward. This reflex is called a “vestibulospinal reflex” and generated at a brain stem (Fig.3-B). In addition, when walking up a slope, adjustment of stretch reflexes of extensor muscles of a supporting leg based on the muscle stiffness model described in 4.2. also assists in keeping body posture flat. As results of experiment, a robot failed in walking up a slope of 12 degrees by using the muscle stiffness model alone, but it succeeded by using both muscle stiffness model and vestibulospinal reflex (Fig.8). In Fig.8, since our robot does not have a head, the inclination of the body is

detected by integrating the angular velocity measured by a rate-gyro. sensor attached to the body.




Fig.8 Results of the experiment involving walking up a slope of 12 degrees by using the muscle stiffness model and a vestibulospinal reflex. CPG output torque and the joint torque, which is the sum of output torques of CPG and reflex mechanisms, of the hip joint and contact sensor value of the left fore leg are shown.

4.3.2 Adjustment of CPG's Parameters by Cerebellum

Although walking up a slope of 12 degrees by using the muscle stiffness model and a vestibulospinal reflex was realized in section 4.3.1., it was not a smooth walking because of occasional slipping and stamping with no progress. In Fig.8, the periods while the contact sensor value is 1, which are shown by vertical broken lines, mean the actual supporting phase of the left fore leg. On the other hand, the periods shown by thick arrows mean the supporting phase in CPG level. We can clearly see in Fig.8 that the actual supporting phase of the leg started largely delayed from CPG supporting phase and continued after the end of CPG supporting phase. Therefore, we can say that the reason of slipping and stamping is that the motion of musculo-skeleton was delayed from states of CPG since walking up a slope had required more thrusting force than walking on flat terrain. This showed that a CPG could not cancel a time lag caused by a lack of thrusting force in walking up a slope in spite of its ability of mutual entrainment with a musculo-skeletal system.

In order to adapt a CPG to a delayed motion of musculo-skeleton, we introduce a cerebellum model for adjustment of CPG's parameters. When a cerebellum detects the delay of joint motion from CPG

state through somatic sensation from peripheral sensors, it autonomously decreases the internal parameter of a CPG (β in Fig.1) in order to increase its period.

As a result of experiment, walking up a slope became much smooth with less slipping and no stamping because entrainment between a CPG and a musculo-skeletal system had been accomplished (Fig.9). We can clearly see in Fig.9 that the actual supporting phase of the leg started a little delayed from CPG supporting phase and finished almost at the same time with the end of CPG supporting phase since the period of a CPG had been increased by adjustment of CPG's parameters.




Fig.9 Results of the experiment involving walking up a slope of 12 degrees by using adjustment of CPG's parameters in addition to using the muscle stiffness model and a vestibulospinal reflex.

When the delay of CPG state from joint motion is detected in walking down a slope, the internal parameter of a CPG (β in Fig.1) is autonomously increased in order to decrease its period.

4.3.3 Coordination of Reflexes by Cerebellum

We implemented adaptive control described in section 4.2., 4.3.1., and 4.3.2. on a quadruped robot. As a result of experiment on irregular terrain shown in Fig.4, it was found that vestibulospinal reflex was too sensitive and disturbed smooth walking except for on a slope. Therefore, we introduce a cerebellum model for coordination of reflexes as non-responsive area of vestibulospinal reflex.

Stretch reflex based on the muscle stiffness model and flexor reflex are always activated. Vestibulospinal reflex is activated when a cerebellum detects inclination of a body larger than threshold for a period longer than a constant period, and inactivated when a cerebellum detects inclination of a body smaller than

threshold. As a result of experiment, by using all adaptive control mechanisms above described, a robot succeeded in walking adaptively and much smoothly (Fig.10) on irregular terrain shown in Fig.4.




Fig.10 Photos of the quadruped walking on a bump:(a) and up a slope:(b).

The cerebellum models for adjustment of CPG's parameters and coordination of reflexes were introduced based on the physiological knowledge that a cerebellum adjusts parameters of controllers and coordinates motion commands to controllers according to changes of external environment based on several sensations.

4.4 Adaptive Control Based on Vision

When the quadruped walks up or down a step, the torque at the hip joints of the supporting legs must be adjusted to keep the angular velocity of the supporting legs around the contact points be constant. This change of motion by torque adjustment of leg joints is made by changing the directive signal to the lower motion controller (u_0 : the external input to a CPG) when the upper controller recognizes a step or an obstacle by vision. Drew et al.[13] proposed a model about the adjustment of the directive signal to a CPG based on visual information (Fig.3-C) by analyzing data from physiological experiments.

In order to examine functions of a CPG in this Drew's model, we placed a step 2cm in height in the way of the quadruped and made the quadruped walk up the step by changing u_0 . The quadruped succeeded in walking up the step when the changing u_0 was employed (Fig.11) and failed when it was not employed. In Fig.11, the amount of increase of u_0 and the time at which u_0 should be increased were determined heuristically through experiments using simple dynamic models.

This results shows that, once a step has been recognized by the upper controller, knowing when and how

much u_0 should be changed is sufficient to generate the signal to the lower motion controller. That is, it is not necessary to direct how the motion of each leg should be changed. This is because a CPG has an ability of automatic interpolation and self stabilization. The fact that a change in only one parameter is enough to achieve a complicated motion such as walking up a step is very interesting and suggests the validity of the Drew's model.




Fig.11 Results of the experiment involving walking up a step 2cm in height: $RFS.x$ and $RFS.N_Tr$ are, respectively, the angle and the output torque of the N.O. of the hip joint of the right foreleg. $RFS.u$ is the joint torque, which is the sum of $RFS.N_Tr$ and the output torque of the reflex mechanism. $RFO.u0$ is a driving input to a N.O. network.

5 Discussion

In order to make the advantages of the biologically-inspired control method clear, let us compare results of the experiments in this study to results from experiments employing the conventional control method based on dynamics[14]. After this comparison, we can remark the following advantages:

- (a) All elements of dynamics and algorithm in trajectory generation and control have been condensed into the parameters of a CPG and reflex mechanisms.
- (b) A CPG characterized by mutual entrainment with a musculo-skeletal system, automatic interpolation, and self stabilization is very useful as a lower controller. Such ability enables flexible and robust dynamic walking on irregular terrain described in section 4.3.2. and 4.4., and the transition of the running gait[10] by modification of a few parameters in a CPG.

These advantages suggest the possibility of adaptive walking on terrain with a high degree of irregularity. For example, parameterization of motion generation and control in (a) simplifies adaptation by learning. CPG as a lower controller in (b) has the ability to make motion adaptation by the upper central nervous system based on vision, vestibular sensation, and somatic sensation relatively simple.

Acknowledgement

This study has been supported by a grant from the TEPCO Research Foundation.

References

- [1] S.Kajita and K.Tani, Control of Dynamic Biped Locomotion Based on Realtime Sensing of the Ground Profile, Journal of RSJ, 14-7, pp.1062-1069, 1996.
- [2] J.Yamaguchi, N.Kinoshita, A.Takanishi and I.Kato, Development of a Dynamic Biped Walking System for Humanoid, Proc. of ICRA96, 1996.
- [3] K.Yoneda and S.Hirose, Tumble Stability Criterion of a Walking Machine, Journal of RSJ, 14-4, pp.517-522, 1996.
- [4] R.D.Beer, H.J.Chiel and L.S.Sterling, An Artificial Insect, American Scientist, 79, pp.444-452, 1991.
- [5] G.Tagat, Y.Yamaguchi and H.Shimizu, Self-organized control of bipedal locomotion by neural oscillators, Biological Cybernetics, 65, pp.147-159, 1991.
- [6] S.Miyakoshi, G.Tagat, Y.Kumiyoshi and A.Nagakubo, Three Dimensional Bipedal Stepping Motion using Neural Oscillators, Proc. of IROS98, pp.84-89, 1998.
- [7] M.A.Lewis, Self-organization of locomotory controllers in robots and animals, Ph.D Dissertation, Electrical Eng., Univ. of Southern California., 1996.
- [8] A.J.Ijspeert, J.Hallman and D.Willshaw, From lampreys to salamanders:evolving neural controllers for swimming and walking, Proc. of SAB98, pp.390-399, 1998.
- [9] W.Ilg, J.Albiez, H.Jedele, K.Berns and R.Dillmann, Adaptive periodic movement control for the four legged walking machine BISAM, Proc. of ICRA99, pp.2354-2359, 1999.
- [10] H.Kimura, K.Sakurama and S.Akiyama: Dynamic Walking and Running of the Quadruped Using Neural Oscillator, Proc. of IROS98, pp.50-57, 1998.
- [11] K.Matsuoka, Mechanisms of Frequency and Pattern Control in the Neural Rhythm Generators, Biological Cybernetics, 56, pp.345-353, 1987.
- [12] K.Akazawa and K.Kato, Neural Network Model of Control of Muscle Force Based on the Size Principle of Motor Unit, Proc. of the IEEE, 78, pp.1531-1535, 1990.
- [13] T.Drew, W.Jiang, B.Kably and S.Lavoie, Role of the motor cortex in the control of visually triggered gait modifications, Can. J. Physiol. Pharmacol. vol.74, pp.426-442, 1996.
- [14] H.Kimura, I.Shimoyama and H.Miura, Dynamics in the dynamic walk of a quadruped robot, RSJ. Advanced Robotics, vol.4, no.3, pp.283-301, 1990.